

TTARP

HD HORIZONTAL SPLITTER

Capable • Affordable • Maintainable



Manufactured in the U.S.A.

A Rugged and Precise Splitter for Splitting and Skinning Low-to-Heavy Density Foams

- 63" cutting width
- 4.9" clearance above and below knife
- 9.8" maximum total clearance
- 4" diameter aggressively knurled feed rollers - servo controlled
- 3.9" wide blade supported by heavy-duty blade guide
- Shapening system with vacuum
- PLC touchscreen control
- Automatic blade advancement
- Quick and easy set-up



Due to our continuous improvement program, specifications and options are subject to change without notice.

TTARP

Ttarp Co.

Toll Free: 800-871-7596
www.Ttarp.com



The TTARP HD splitter gives you in-house capability to respond to the needs of your customers quickly, while helping you reduce material and inventory costs

Specifications

Cutting Width:

- 63" (160.0 cm)

Overall Dimensions:

- 119" L x 207" W x 86" H
(302cm x 526cm x 219cm)

Blade Wheels:

- 30" (76.2cm)

Blade:

- .050" x 3.9" W x 30'-1" L
(.12cm x 10cm x 918.1cm)

Blade Drive:

- Qty two (2) 7.5 gear motors

Pinch Roller Drive:

- 15 HP Gear motor (drive shafts)
- Qty two (2) 4HP Servo motors for up/down knurled roller position control
- Qty two (2) 2HP blade sharpeners

Voltage:

- 460 VAC, 3-phase

Features

- PLC Touchscreen
- Blade sharpening system
- Precise knurled roller position via servo
- Auto blade advancement
- Adjustable knurled roller speed
- Adjustable blade speed



Ttarp designs and manufactures a complementary range of capable, affordable, and maintainable fabricating equipment. Contact us for more information.